

## CO29 • 21" Marine Combo® Model • Marine Series

## **FEATURES & BENEFITS**







BLACK SOLID

WHITE SOLID

## • Refrigerator volume of 2.1 cu ft holds up to 24 bottles (12 oz) or 44 cans (12 oz)

- Mechanical Dial Control is conveniently located on the grille
- Temperature range: 34°F 45°F
- Produces and stores up to 8 lbs of ice per day
- Crescent ice cube dimensions: 1/2" W x 3/4" H x 1/2" L
- Available in 115 or 220 240 volts

# INTERIOR/EXTERIOR • No drain required

- Two removable tempered glass shelves
- Two fixed storage compartments in door
- Door swing is field reversible
- Standard travel package includes door latch, ensuring safe-at-sea storage
- Corrosion and UV resistant components provide product longevity in harsh environments

# INTEGRATION

- Unit is designed to be built-in or can be freestanding
- Available in the following finishes: Black or White
- Accepts a 1/4" custom panel

## **MODEL DETAILS**

Model	Voltage	Door Swing	Finish	Shipping Weight
ULN-CO29B-03A	115	Right-Hand Hinge	Black Solid	94 lbs
ULN-CO29B-20A	220 - 240	Right-Hand Hinge	Black Solid	94 lbs
ULN-CO29W-03A	115	Right-Hand Hinge	White Solid	94 lbs
ULN-CO29W-20A	220 - 240	Right-Hand Hinge	White Solid	94 lbs

## **ACCESSORIES**

Model	Description	Finish	Shipping Weight
WATERHOOKUP	Braided water supply line kit	na	2 lbs


# PERFORMANCE




# Marine Series • 21" Marine Combo® Model • CO29

### **DIMENSIONS**

Dimensions shown apply to all finishes.



## **CABINET CUT-OUT**



## **INSTALLATION NOTES**

Cutout includes the additional  $\frac{1}{4}$ " width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

UL listing only applies to 115 v models.

Please visit u-line.com to view this model's User Guide. All specifications are subject to change without notice.

### **SPECIFICATIONS**

Model       CO29         Amps: Running (115 v)       2.5         Amps: Running (220 - 240 v)       1.2         Amps: Max Start Up (115 v)       18         Amps: Max Start Up (220 - 240 v)       6         Capacity: Bottle (12 oz)       24         Capacity: Can (12 oz)       44         Capacity: Volume (cu ft)       2.1         Control Type       Mechanical Dial         Defrost Type       Manual         Dimensions: Product Depth       23" / 584 mm         Dimensions: Product Height       28 ½" / 724 mm         Dimensions: Product Width       20 %" / 530 mm
Amps: Running (220 - 240 v)  Amps: Max Start Up (115 v)  Amps: Max Start Up (220 - 240 v)  Capacity: Bottle (12 oz)  Capacity: Can (12 oz)  Capacity: Volume (cu ft)  Control Type  Mechanical Dial  Defrost Type  Minual  Dimensions: Product Depth  Dimensions: Product Height  1.2  1.2  1.2  1.2  1.2  1.2  1.2  1.
Amps: Max Start Up (115 v)  Amps: Max Start Up (220 - 240 v)  Capacity: Bottle (12 oz)  Capacity: Can (12 oz)  Capacity: Volume (cu ft)  Control Type  Dimensions: Product Depth  Dimensions: Product Height  18  44  24  Capacity: Value (12 oz)  Mechanical Dial  Manual  Dimensions: Product Depth  28 ½" / 724 mm
Amps: Max Start Up (220 - 240 v) 6  Capacity: Bottle (12 oz) 24  Capacity: Can (12 oz) 44  Capacity: Volume (cu ft) 2.1  Control Type Mechanical Dial  Defrost Type Manual  Dimensions: Product Depth 23" / 584 mm  Dimensions: Product Height 28 ½" / 724 mm
Capacity: Bottle (12 oz)  Capacity: Can (12 oz)  Capacity: Volume (cu ft)  Control Type  Mechanical Dial  Defrost Type  Manual  Dimensions: Product Depth  Dimensions: Product Height  24  44  2.1  Mechanical Dial  Manual  23" / 584 mm  Dimensions: Product Height
Capacity: Can (12 oz)  Capacity: Volume (cu ft)  Control Type  Mechanical Dial  Defrost Type  Manual  Dimensions: Product Depth  Dimensions: Product Height  28 ½" / 724 mm
Capacity: Volume (cu ft)  Control Type  Mechanical Dial  Defrost Type  Manual  Dimensions: Product Depth  Dimensions: Product Height  2.1  Mechanical Dial  23" / 584 mm  28 ½" / 724 mm
Control Type Mechanical Dial  Defrost Type Manual  Dimensions: Product Depth 23" / 584 mm  Dimensions: Product Height 28 ½" / 724 mm
Defrost Type Manual  Dimensions: Product Depth 23" / 584 mm  Dimensions: Product Height 28 ½" / 724 mm
Dimensions: Product Depth 23" / 584 mm  Dimensions: Product Height 28 ½" / 724 mm
Dimensions: Product Height 28 ½" / 724 mm
-
Dimensions: Product Width 20 1/8" / 530 mm
ENERGY STAR na
Ice Production Per Day 25 lbs
Ice Storage 13 lbs
Product Weight: Max 85 lbs
Refrigerant Type R134A
Sabbath (Star K Certified) No

## **ELECTRICAL REQUIREMENTS**

This unit requires a grounded a polarized 115 VAC,  $60~{\rm Hz}$ ,  $15~{\rm A}$  power supply (normal household current).



Residential